

IN1188HD

Ultra-Portable LED Projector

Part #: IN1188HD

InFocus

The IN1188HD ultra-portable projector is built to perform, with HDMI input, high brightness, ultra-long-lasting images, and unbeatable quality and color. Featuring a compact, light weight design, the IN1188HD is perfect for business travelers, or anyone who needs to take their presentation on the road.

Key Features

- ◆ Quantum Color Engine for vivid, ultra-long-lasting images
- ◆ Amazing 30,000-hour light source
- ◆ Green, mercury-free technology
- ◆ 3000 lumens and full HD resolution
- ◆ Wireless, PC-less on-board document viewer with QuadView (with wireless adapter)
- ◆ Support for AirPlay and MiraCast



Quantum Color Engine

The IN1188HD is powered by the InFocus Quantum Color Engine for exceptional image quality over years of continuous operation. The Quantum Color Engine is based on solid-state illumination technology, and is tested for over 200 unique color parameters to ensure the most vivid images possible. A massive color gamut, up to 40% bigger than leading competitors, and high color luminosity ratio bring your screen to life. With no color decay, you can enjoy remarkable images for over 3 years of 24/7 operation or over 10 years of business hour operation.

Superior Images

Get quality images and true-to-life colors with DLP technology with InFocus BrilliantColor implementation. 3,000 lumens mean bright, clear images even with the lights on, and 1,000,000:1 contrast ratio adds sharpness with darker blacks and whiter whites.

Greener Technology, Greater ROI

Solid-state technology means your projector will last an amazing 30,000 hours, with an environmentally friendly mercury-free design. No lamps to replace means less hassle and fewer added expenses over time

Specifications*

Projector

IN1188HD

Resolution – Native

Full HD (1920 x 1080)

| Projector | IN1188HD |
|-----------------------------------|---|
| Display Technology | DLP with LED light source |
| Video Standard Compatibility | NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, SECAM, 480i, 480p, 576i, 576p, 720p, 1080i, 1080p |
| Speakers | Mono 3W x 1 |
| Lamp Brightness | 3,000 lumens |
| Lamp Life | 30,000 hours |
| Lamp Power | 106W |
| Contrast Ratio | 150,000:1 |
| Number of Colors | 1.08 billion |
| Synch Scan Frequency – Horizontal | 15 ~ 103 KHz |
| Synch Scan Frequency – Vertical | 24 ~ 120 KHz |
| Aspect Ratio | 16:9 |
| Aspect Ratio Compatibility | 4:3, 16:10, 2.35:1, 1:1, 2:1, 13:9, 15:9, 5:4 |
| Projection Lens F-Stop – Minimum | 1.70 |
| Image Size – Minimum | 30 in |
| Image Size – Maximum | 300 in |
| Projection Offset | 103% |
| Keystone Correction | ± 40° |
| Connectors – Inputs | 3.5mm audio, Composite video, USB A x2, HDMI, VGA |
| Connectors – Outputs | 3.5mm audio output |
| Audible Noise | < 33 dBA at 0°F / -17.8°C |
| Audible Noise – Eco Mode | < 26 dBA at 0°F / -17.8°C |
| Included Accessories | Power cord, Remote, HDMI Cable, Documentation, Quick Start Guide, Carrying case, User Manual (CD), Lens cap |
| 3D Support | 1080p @ 60Hz, All HDMI 1.4a 3D formats, DLP Link 3D glasses required |
| Product Warranty | 2 years |
| Video Player Compatibility | AVI, MKV, MP4, MPEG-1 (MPG, MPEG), WMV, MOV |
| Photo Viewer Compatibility | JPEG and JPG, Bitmap (BMP) |
| Music Player Compatibility | MP3, WMA, AAC, WAV |
| Power Consumption | 215.0W max |
| Power Consumption – Standby Mode | 0.5W max |
| Power Standard | AC 100 to 240V, 50/60 |
| Documentation Languages | English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Arabic, Indonesian, Portuguese |
| Menu Languages | English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Russian, Polish, Turkish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, Thai |
| Operating Pitch/Roll | 360 degree operation |
| Illumination Technology | LED, InFocus Quantum Color Engine |
| Display Technology | DLP .47" S410 |
| Uniformity | JBMA 85% ANSI 70% |
| Zoom Ratio | Fixed |
| Throw and Zoom | |
| Throw Distance – Minimum | 0.8 m |
| Throw Distance – Maximum | 8.0 m |
| Throw Ratio | 1.20:1 |
| Shipping | |
| Product Dimensions | 2.2 x 11.7 x 7.9 in / 55.9 x 297.2 x 199.9 mm |
| Product Weight | 4.4 lbs / 2 kg |

* Product specifications, terms, and offerings are subject to change at any time without notice.

Accessories

Universal Projector Ceiling Mount (PRJ-MNT-UNIV)
 InFocus Standard Replacement Remote (HW-NAVIGATOR-5)
 SimpleShare Presentation System (INA-SIMPS1)
 LiteShow 4 DB+ Dual Band Wireless Adapter (INLITESHOW4DB+)
 LiteShow Mount Adapter (PRJ-MNT-LS3)
 SimpleShare Touch Presentation System (INA-SIMINT1)

SimpleShare (INA-SIMS1)

DLP Link 3D Glasses by XPAND (X103-EDUX3-R1)

Soft Projector Carry Case (CA-SOFTCASE-VAL3)

Manual Pull Down Projector Screen: 92 in., 16:9 (SC-PDHD-92)

Manual Pull Down Projector Screen: 106 in., 16:9 (SC-PDHD-106)

Manual Pull Up Projector Screen: 73 in., 16:9 (SC-PUW-73)

Manual Pull Up Projector Screen: 90 in., 16:9 (SC-PUW-90)

1 Year Extended Warranty for IN1XXX, IN2XXX, IN3XXX Projectors (EPW-PJM1)

2 Year Extended Warranty for IN1XXX, IN2XXX, IN3XXX Projectors (EPW-PJM2)