

Key **Features**

- 4,500 ANSI Lumens, offering clear images in any environment
- Up to 300" ultra large screen with lower cost-per-inch
- Easy and flexible connection: dual HDMI ports, USB Type-A port
- Vivid colors with
 ViewSonic's SuperColor™
 Technology
- Convenient software updates for projectors via USB connection



Product **Description**

The PA700X is ViewSonic's high brightness XGA business/education projector. With 4,500 ANSI Lumens of high brightness, the projector offers clear images of up-to-300" large screen in meeting rooms, classrooms, or any other bright environment. The dual HDMI ports allow you to flexibly connect to multiple devices, easily switching between content sources. The USB Type-A port can supply power to HDMI wireless dongles, making wireless content streaming more convenient. The projector also allows software updates via USB cable connection with simply your laptops, skipping trips to service centers.



Visit Us

www.viewsonic.com

SPECIFICATION STANDARD ACCESSORY 1024x768 Power Cord: Native Resolution: Brightness: 4500 (ANSI Lumens) VGA Cable: 1 Contrast Ratio with SuperEco Mode: Remote Control: 12500:1 QSG: Yes 1.07 Billion Colors Display Color Air Filter: Yes (CN Only) Light Source Type 240W UHP Lamp Warranty Card: Yes (CN Only) Light Source Life (hours) with Normal Mode: 4000 **OPTIONAL ACCESSORY** Light Source Life (hours) with SuperEco Mode: Lamp/Light Source: RLC-128 12000 Air Filter: RSPL F=2.42-2.53, f=21.85-24.01mm Lens: Wall/Ceiling Mount: PJ-WMK-007 Projection Offset 115%+/-5% Carry Bag: PJ-CASE-008 Throw Ratio 1.94-2.16 Optical Zoom: Digital Zoom: 0.8x-2.0x Image Size: 30"-300" 1.18m-13.17m (100"@3.94m) Throw Distance Kevstone +/- 40° (V) Audible Noise (Normal): 34dB Audible Noise (Eco): 25dB 33.2ms Input Lag VGA(640 x 480) to FullHD(1920 x Resolution Support: 480i, 480p, 576i, 576p, 720p, 1080i, 1080p HDTV Compatibility: Video Compatibility: NTSC, PAL, SECAM Horizontal Frequency: 15K-102KHz Vertical Scan Rate: 23-120Hz INPUT Computer in (share with component): 2 (HDMI 1.4/ HDCP 1.4) HDMI: Audio-in (3.5mm): OUTPUT Monitor out: Audio-out (3.5mm): Speaker: 3W USB Type A (Power): 1 (5V/1.5A) CONTROL RS232 (DB 9-pin male): USB Type A (Services): (share with USB A Output) OTHERS 100-240V+/- 10%, 50/60Hz (AC in) Power Supply Voltage: Power Consumption: Normal: 295W Standby: <0.5W Operating Temperature: 0~40°C Carton: Brown Net Weight: 2.70kg Gross Weight: 3.80Kg Dimensions (WxDxH) with Adjustment Foot: 309x234x115mm Packing Dimensions: 400x337x168mm

Copyright © ViewSonic Corporation 2000-2023. All rights reserved.

English, German, French, Swedish, Spanish, Portuguese, Polish, Dutch, T. Chinese, S.Chinese, Finnish, Korean, Russian, Hungarian, Czech, Arabic, Thai, Turkish, Vietnamese, Indonesian, Greek, Italian, Total 22 languages

English, S-Chinese, T-Chinese, Finnish,French,German,Italian,Japanese,Korean,Polish,Portuguese,Russian,Spanish,Swedish,Turkish,

Total 15 languages

OSD Language:

User Guide Language: