

SCREENPLAY GENESIS II SERIES SP224ST



WXGA - 3800 ☀ - 4:3 Aspect Ratio

The ScreenPlay Genesis II DLP projectors offer outstanding ultra-long lamp life, high brightness, and superb connectivity, which includes 2x HDMI ports. Designed for classroom, office, and home use, they provide:

- Perfect images.
- Vibrant colours.
- Outstanding readability and contrast
- Compact and lightweight form.
- Versatile portable display solution.

Short-throw models for education for use with interactive whiteboards add further versatility to Genesis II.

The complete Genesis Series is also easy on the eye with its sleek matte white finish, understated branding with accessories to match.

Features

Full 3D

Display 3D content from almost any 3D source, including 3D Blu-ray players and the latest game consoles.

USB-A Power for Devices

Power your external devices like Google Chromecast with Amazon TV with the convenient USB-A input on the projector.

Industry-leading Lamp Life

An unprecedented 15,000 hours of lamp life when used in Dynamic Mode. With no filters to replace.

High Brightness

Get better, brighter images on any surface, in any light, with 4000 lumens on the standard throw models and 3800 lumens on short throw models.

Advanced Digital Image Correction

With the new digital edge masking and image shift features – we make getting those final image adjustments perfect.

24/7 Operation

They are designed to operate 24 hours a day in standard orientation. Perfect for applications where prolonged periods of use are required.

Image

Projection Technology	Texas Instruments DLP®
Panel Size	0.65" DMD
Native Resolution	XGA
Pixels	1024 x 756
Aspect Ratio	4:3
Contrast Ratio	30000:1

Brightness (Lumens)	3800
Light Source	UHP Lamp
Light Source Life Maximum Hours	15000
Maximum Supported Resolution	1920 x 1200
Horizontal Sync. Range (KHz)	15 ~ 97.55
Vertical Sync. Range (Hz)	54 ~ 85
Uniformity (%)	80

Optical

Lens	Fixed 1:1
Lens Zoom Adjustment	-
Optional Lenses	-
Image Offset (%)	112.4
Focal Length (mm)	7.15
F-Stop	2.8
Vertical Lens shift (%)	-
Horizontal Lens shift (%)	-
Keystone Adjustment	Manual / Automatic
Vertical Keystone Correction	± 20°
Horizontal Keystone Correction	-
Projection Factor	0.52:1
Projection Distance (Meters/Feet)	0.4 ~ 3.37 / 1.31 ~ 11.05
Optical Zoom	Fixed 1:1
Digital Zoom Demagnification / Magnification	0.8x ~ 2.0x
Focus Adjustment	Manual

Connectivity

Inputs	Mini D-sub 15-pin (VGA), S-Video, 2 x HDMI™ 1.4, 3.5 mm Stereo Mini Jack, USB-A for Service
Outputs	3.5 mm Stereo Mini Jack, Powered USB-A for Wireless Dongle, Mini D-sub 15-pin (VGA)
Networking & Control	RS232
Embedded System	-
3D	Full 3D All Major Formats

Power

Power Supply	100 ~ 240 V AC; 50 ~ 60 Hz
Power Consumption Max (W)	267
Power Consumption Min. (W)	210
Power Consumption Network Standby (W)	-
Power Consumption Standby (W)	<0.5

General

Product Dimensions (W x H x D) (mm / in)	313 x 236 x 96.4 / 12.4 x 9.3 x 3.8
Product Weight (Kilograms/Pounds)	2.9 / 6.4
Packaged Dimensions (L x W x H) (mm / in)	395 x 337 x 166 / 15.6 x 13.3 x 6.5
Packaged Weight (Kilograms/Pounds)	4.1 / 9.0

Fan Noise (dB)	27
Audio (W)	1 x 10
Operating Temperature (Celsius/Fahrenheit)	5 ~ 40 / 41 ~ 104
Operating Humidity (%)	10 ~ 85
Max Operating Altitude (meters / feet)	3048 / 10000
Storage Temperature (Celsius/Fahrenheit)	-10 ~ 60 / 14 ~ 140
Storage Humidity (%)	10 ~ 85
Security	Kensington Security Slot™, PIN Code Lock & Timer
Safety and Regulatory	CB, CE, EAC, cTUVus, CCC, FCC, UKCA, NOM, PSB, BIS
Environmental	WEEE, EU RoHS, China RoHS, CEL, CECP

Copyright © 2022, InFocus and its logo is a registered trademark of InFocus Corporation. Maxnerva Technology Services Limited is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted; all specifications are subject to change without notice. All images are for representation purposes only and may be simulated.