


Highlights:

- Stores up to 42 units of 19" Equipment
- Integrated ventilation grid on top
- 50 mm Wheels + leveling feet included
- Removable sides for easy installing & cabling
- Punched square holes for use with snap-in cage nuts
- Front and rear in depth adjustable 19" profiles (max 740 mm)
- Reversible door position
- Mesh perforation with hexagonal pattern
- Swing handle with cylinder lock

The SPR842GG is a professional 19" rack compliant to the ANSI/EIA RS-310D, DIN41491 and IEC60297 standards. A cold rolled steel 2 mm thick frame and 1,2 mm thick plates provide a solid and stable construction making it suitable for heavy equipment, storing up to 42 units inside. The SPR842GG comes fully assembled including 50 mm wheels for easy moving and adjustable feet for fixing and levelling once correctly positioned. The 19" mounting profile with punched square holes for use with snap-in cage nuts in combination with the printed unit measurement indicators ensure an easy fitting of the equipment. Adjustable 19 " profiles provide great flexibility for installing equipment depending on its depth.

The SPR842GG comes with 2 perforated steel grill doors (front and rear). The mesh perforation with hexagonal pattern provides an optimal air flow through the cabinet. The swing handle with cylinder lock safely locks the equipment inside.



Product Features:

Unit height		42 HE
Colours		Black (RAL9004)
Max. usable depth		740 mm
Dimensions		600 x 1985 (2055) x 800 mm (W x H (incl. feet) x D)
Wheel	Diameter	50 mm
Static load capacity (adjustable feet)		800 kg
Dynamic load capacity (transport castors)		400 kg
Weight		88 kg
Accessories	Included	4 x Key for sidepanel lock
		1 x Allen key
		4 x Levelling feet
		4 x Key for front/back door
		20 x KS600
		20 x KM600
	Optional	KS600 - M6 x 16 mm bolt DIN7985 Black
		KM600 - M6 Cage nuts

Architects' and Engineers' Specifications:

The rack shall have the following dimensions: Height 1985 mm, Depth 800 mm, Width 600 mm, have a Weight of 98 kg and hold up to 42 units. The rack shall comply with ANSI/EIA RS-310D, DIN41491 and IEC60297 standards. 50 mm wheels will be included as well as levelling feet. The frame of the rack shall be constructed out of cold rolled steel of 2 mm thick while for the other parts a thickness of 1.2 mm shall be used. These parts shall have a textured black powder coating (RAL9004) colour. The mounting rail shall be adjustable in depth on the front and rear side and have unit measurement indicators on the front side. The rack shall include 2 perforated steel grill doors, both equipped with a standard key lock. Sides of the rack shall be removable and the top shall have a ventilation grid.