

IN119HDxa Projector

A Stunning Home Entertainment Experience

Part #: IN119HDxa

Whether you're screening a blockbuster, hosting a SuperBowl party, or facing off in a cutting-edge video game, everything comes to life in stunning HD with the high brightness and 3D capability of the IN119HDxa home projector.



Key Features:

- Full 1920 x 1080 HD resolution for exceptional image quality
- 3,600 lumens and high 28,000:1 contrast ratio make details pop
- Vivid and accurate color with BrilliantColor technology
- Display 3D content from Blu-ray, game consoles, and more

1080p HD resolution

Watch your favorite movies, sports, and games as they were meant to be seen, in full native 1080p resolution (16:9 aspect ratio). With no scaling or altering of the image, your picture will look better than ever and larger than life – at an affordable price.

HDMI CEC Compatible

The IN119HDxa is an HDMI Consumer Electronics Control (CEC) compatible device, so you can control it, and up to 14 other HDMI CEC compatible devices, with one remote.



3D

Advanced 3D Support

Powered by the latest DLP technology, the IN119HDxa displays stunning 3D content from PCs, Xbox, PlayStation, Blu-ray, and many other sources. Just add 144Hz DLP Link 3D glasses (sold separately) to seamlessly synchronize with the image for an awesome 3D experience.

High Brightness and High Contrast

Meticulous attention to detail brings out amazing life-like details to create a fully immersive entertainment experience at home. 3,600 lumens give you images that come in bright and clear. 28,000:1 contrast ratio adds sharpness and depth with darker blacks and whiter whites.

Specifications*

| | IN119HDxa |
|----------------------------------|---|
| Display Technology | Texas Instruments DLP® 0.65" DMD with DarkChip3™ 1080p Technology |
| Resolution | Full HD (1920 x 1080) 1080p |
| Brightness (Normal/Eco) | 3,600 / 2,800 lumens |
| Contrast Ratio | 28,000:1 |
| Lamp Life (Normal/Eco/Dynamic) | 5,000 / 7,000 / 15,000 hours |
| Throw Ratio | 1.124~1.47(D/W) @ 60" |
| Throw Distance (focus range) | 1.2m to 7.5m |
| Zoom Type | 1.3:1 |
| I/O Connectors | HDMI x2 (1.4a 3D support) + MHL v2.1, Audio Out 3.5mm, 12V trigger, 3D-Sync, USB service |
| Speaker (Watts) | 10 |
| Keystone Correction | ± 40° Vertical |
| Weight | 5.5 lbs / 2.5 kg |
| Dimensions (W x D x H) | 4 x 12.4 x 8.8 in / 101.6 x 315 x 223.5 mm |
| Aspect Ratio | 16:9 Native, 16:10/4:3 Compatible |
| Offset | 116% ±5% |
| Projection Screen Size | 1.06 - 7.75m (41.8" - 305") Diagonal 16:9 |
| Projection Distance | 1.5 - 10 m |
| Projection Lens (f-stop) | 2.43 (Wide.)~ 2.78 (Tele) |
| Focus (manual/power) | Manual |
| Image Width | 36.95" ~ 301.4" optimized @ 60" |
| Lens Shift H | N/A |
| Lens Shift V/Offset | 16% |
| Uniformity | 80% |
| Maximum Resolution | 1080p |
| Computer Compatibility | UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, PC, Mac |
| Video Compatibility | PAL, NTSC, SECAM, 480i/p, 576i/p, 720p, 1080i, 1080p |
| 3D Compatibility | 1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 |
| Horizontal Scan Rate | 15.375~91.146 KHz |
| Horizontal Scan Rate | 24 ~ 85Hz (120Hz for 3D) |
| Displayable Colors | 1073.4 Million |
| Noise Level (Eco mode) | 24dB |
| Power Supply | 100-240V, 50-60Hz |
| Lamp Type (Normal, Eco, Dynamic) | 195 / 160 / 83W |
| Operating Conditions | 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m |
| Security | Security bar, Kensington lock, password protection |
| On Screen Display | 27 Languages: English, French, German, Spanish, Italian, Portuguese, Dutch, Swedish, Finnish, Greek, Danish, Norwegian, Polish, Russian, Simplified_Chinese, Traditional_Chinese, Korean, Arabic, Japanese, Thai, Hungarian, Czechoslovak, Turkish, Vietnamese, Farsi, Romanian, Indonesian |
| Standard Accessories | Power cord, remote control, VGA cable, documentation |
| Projection method | Front, rear, ceiling mount, table top |

*Product specifications, terms, and offerings are preliminary and subject to change at any time without notice.

Optional Accessories

Replacement Lamp (SP-LAMP-097)
 Universal Ceiling Mount (PRJ-MNT-UNIV)
 LiteShow 4 DB+ Dual Band Wireless Adapter (INLITESHOW4DB+)
 LiteShow Mount (PRJ-MNT-LS3)

Soft Carry Case (CA-SOFTVAL-2)
 DLP Link 3D Glasses (X103-EDUX3-R1)
 Extended Warranties (EPW-PJV1, EPW-PJV2)