

NovoTouch

LK6530i



Model Name	NovoTouch LK6530i
Display Technology	Backlit LED (IPS Panel)
Panel Size; Aspect Ratio	65", 16:9
Brightness	350cd/m ²
Contrast Ratio (Typical)	1,200:1
Native Resolution	4K Ultra-HD (3840 x 2160)
Viewing Angle (Horiz/Vert)	178°/178°
Refresh Rate (Hz)	60Hz
Display Color (Bit)	1.06 billion (10-bit)
Orientation	Landscape
Touch Technology	Infrared Touch
Touch Points	10 Writing, 20 Touch
Surface Protection	4mm Thick Toughened Glass (Level 7H on Mohs Scale of Mineral Hardness)
Minimum Touch Object	Single-Touch ≥Φ6mm and Multi-Touch ≥Φ8mm
Touch Tools	Finger, Stylus, Glove, Opaque Objects
Gestures Supported	Yes
System Version	Android™ v6.0
CPU	RK3399, Dual-Core ARM® Cortex® A72 and Quad Core ARM® Cortex® A53
GPU	Mali™ T860
RAM	4GB DDR3
Internal Storage	16GB
OS Compatibility	Windows® (Windows 7 and above: Driver Free), macOS (10.10 and above), Android™ (2.2/2.3/4.0/4.1/4.2 (Kernel v3.5 and above - Driver Free), Chrome (v39 and above), Linux (Kernel v3.5 and above)
I/O Ports	HDMI v2 (x1), HDMI v1.4 (x2), DisplayPort (x1), VGA-In (x1), Audio-In (3.5mm) (x1), AV-In (x1), HDMI-Out (1080P) (x1), Audio-Out (3.5mm) (x1), Coaxial-Out (RCA) (x1), LAN (RJ45) (x1), RS232 (x1), USB Type A 2.0 (x4), USB Type A 3.0 (x2), USB Type B (x2)
Internal Speakers	12W (x2) (Stereo)
Power Supply (Internal)	AC 100-240V, 50/60Hz
Dimensions	1,521 x 915 x 99 mm
Weight (Net)	47 kg
Weight (Gross)	57 kg
Accessories (Standard)	AC Power Cord, VGA Cable, USB Cable, Audio Cable, Stylus (x3), Remote Control, Wall Mount Kit, Documentation Kit

NovoTouch

LK7530i



Model Name	NovoTouch LK7530i
Display Technology	Backlit LED (IPS Panel)
Panel Size; Aspect Ratio	75", 16:9
Brightness	330cd/m ²
Contrast Ratio (Typical)	1,200:1
Native Resolution	4K Ultra-HD (3840 x 2160)
Viewing Angle (Horiz/Vert)	178°/178°
Refresh Rate (Hz)	60Hz
Display Color (Bit)	1.06 billion (10-bit)
Orientation	Landscape
Touch Technology	Infrared Touch
Touch Points	10 Writing, 20 Touch
Surface Protection	4mm Thick Toughened Glass (Level 7H on Mohs Scale of Mineral Hardness)
Minimum Touch Object	Single-Touch ≥Φ6mm and Multi-Touch ≥Φ8mm
Touch Tools	Finger, Stylus, Glove, Opaque Objects
Gestures Supported	Yes
System Version	Android™ v6.0
CPU	RK3399, Dual-Core ARM® Cortex® A72 and Quad Core ARM® Cortex® A53
GPU	Mali™ T860
RAM	4GB DDR3
Internal Storage	16GB
OS Compatibility	Windows® (Windows 7 and above: Driver Free), macOS (10.10 and above), Android™ (2.2/2.3/4.0/4.1/4.2 (Kernel v3.5 and above - Driver Free), Chrome (v39 and above), Linux (Kernel v3.5 and above)
I/O Ports	HDMI v2 (x1), HDMI v1.4 (x2), DisplayPort (x1), VGA-In (x1), Audio-In (3.5mm) (x1), AV-In (x1), HDMI-Out (1080P) (x1), Audio-Out (3.5mm) (x1), Coaxial-Out (RCA) (x1), LAN (RJ45) (x1), RS232 (x1), USB Type A 2.0 (x4), USB Type A 3.0 (x2), USB Type B (x2)
Internal Speakers	12W (x2) (Stereo)
Power Supply (Internal)	AC 100-240V, 50/60Hz
Dimensions	1,762 x 1,034 x 101 mm
Weight (Net)	60 kg
Weight (Gross)	78 kg
Accessories (Standard)	AC Power Cord, VGA Cable, USB Cable, Audio Cable, Stylus (x3), Remote Control, Wall Mount Kit, Documentation Kit

NovoTouch

LK8630i



Model Name	NovoTouch LK8630i
Display Technology	Backlit LED (IPS Panel)
Panel Size; Aspect Ratio	86", 16:9
Brightness	330cd/m ²
Contrast Ratio (Typical)	1,200:1
Native Resolution	4K Ultra-HD (3840 x 2160)
Viewing Angle (Horiz/Vert)	178°/178°
Refresh Rate (Hz)	60Hz
Display Color (Bit)	1.06 billion (10-bit)
Orientation	Landscape
Touch Technology	Infrared Touch
Touch Points	10 Writing, 20 Touch
Surface Protection	4mm Thick Toughened Glass (Level 7H on Mohs Scale of Mineral Hardness)
Minimum Touch Object	Single-Touch ≥Φ6mm and Multi-Touch ≥Φ8mm
Touch Tools	Finger, Stylus, Glove, Opaque Objects
Gestures Supported	Yes
System Version	Android™ v6.0
CPU	RK3399, Dual-Core ARM® Cortex® A72 and Quad Core ARM® Cortex® A53
GPU	Mali™ T860
RAM	4GB DDR3
Internal Storage	16GB
OS Compatibility	Windows® (Windows 7 and above: Driver Free), macOS (10.10 and above), Android™ (2.2/2.3/4.0/4.1/4.2 (Kernel v3.5 and above - Driver Free), Chrome (v39 and above), Linux (Kernel v3.5 and above)
I/O Ports	HDMI v2 (x1), HDMI v1.4 (x2), DisplayPort (x1), VGA-In (x1), Audio-In (3.5mm) (x1), AV-In (x1), HDMI-Out (1080P) (x1), Audio-Out (3.5mm) (x1), Coaxial-Out (RCA) (x1), LAN (RJ45) (x1), RS232 (x1), USB Type A 2.0 (x4), USB Type A 3.0 (x2), USB Type B (x2)
Internal Speakers	12W (x2) (Stereo)
Power Supply (Internal)	AC 100-240V, 50/60Hz
Dimensions	1,988 x 1,178 x 99.6 mm
Weight (Net)	78 kg
Weight (Gross)	105 kg
Accessories (Standard)	AC Power Cord, VGA Cable, USB Cable, Audio Cable, Stylus (x3), Remote Control, Wall Mount Kit, Documentation Kit

NovoTouch

LK9810i



Model Name	NovoTouch LK9810i
Display Technology	Backlit LED (IPS Panel)
Panel Size; Aspect Ratio	98", 16:9
Brightness	440cd/m ²
Contrast Ratio (Typical)	1,300:1
Native Resolution	4K Ultra-HD (3840 x 2160)
Viewing Angle (Horiz/Vert)	178°/178°
Refresh Rate (Hz)	60Hz
Display Color (Bit)	1.06 billion (10-bit)
Orientation	Landscape
Touch Technology	Infrared Touch
Touch Points	5 Writing, 10 Touch
Surface Protection	4mm Thick Toughened Glass (Level 7H on Mohs Scale of Mineral Hardness)
Minimum Touch Object	Single-Touch ≥Φ6mm and Multi-Touch ≥Φ8mm
Touch Tools	Finger, Stylus, Glove, Opaque Objects
Gestures Supported	Yes
System Version	Android™ v4.2.1
CPU	ARM® Cortex® A9 Dual Core CPU
GPU	Quad Core GPU
RAM	1.5G RAM
Internal Storage	8GB
OS Compatibility	Windows® (Windows 7 and above: Driver Free), macOS (10.10 and above), Android™ (2.2/2.3/4.0/4.1/4.2 (Kernel v3.5 and above - Driver Free), Chrome (v39 and above), Linux (Kernel v3.5 and above)
I/O Ports	HDMI v1.4 (x1), HDMI v1.3 (x3), AV-In (x1), VGA-In (x3), AudioIn (x3), VGA-Out (x1), Audio-Out (3.5mm (x1)), Coaxial-Out (RCA) (x1), LAN (RJ45) (x1), RS232 (x1), USB Type A 2.0 (x4), USB 3.0 (x1), USB Type B (x2)
Internal Speakers	10W (x2) (Stereo)
Power Supply (Internal)	AC 100-240V, 50/60Hz
Dimensions	2,257 x 1,335 x 121 mm
Weight (Net)	150 kg
Weight (Gross)	200 kg
Accessories (Standard)	Touch Screen Panel, NovoEnterprise NE3000EU, Wall Mount WIB9060A, Documentation Kit, AC Power Cord, VGA Cable, USB Cable, Audio Cable, Stylus (x3), Remote Control with Batteries.

NovoTouch

Vivitek VKW21 PC Module



Model Number	Vivitek VKW21		
Product Compatibility	LK6530i, LK7530i, LK8630i		
Type	Detachable PC Module		
Interface	120PIN Connector		
Hardware	CPU	Intel® Core™ i5	
	RAM	DDR4 4GB	
	Internal Storage	SSD 128GB	
	Graphics	Integrated Intel® HD Graphics	
	Chipset	Intel® H110 Express	
	Sound Card	Integrated High Definition Audio Stereo	
	Networking	Integrated 10/100/1000Mbps Adaption	
Connectivity	Input	Audio	Microphone-In (3.5mm)
	Output	Display	HDMI 1.4, VGA-Out, DisplayPort
		Audio	Earphone (3.5mm)
	Control	RJ45	
	USB	USB 3.0 (x6)	
Wireless	IEEE 802.11 a/c (2.4GHz/5GHz)		
Recommended Operating System	Windows 10 (not included)		
LED Indicator	Green LED:Hard Disk is Running, Red LED:Power is On		
Environmental Conditions	Operating Temperature	0°C - 40°C (32°F - 104°F)	
	Operating Humidity	10% - 90%	
	Storage Temperature	-20°C - 60°C (-4°F - 140°F)	
	Storage Humidity	10% - 90%	
Power	Power Supply Mode	Internal Power Supply Module	
	Power Requirements	100V-240V AC 50/60Hz	
	Max Power	95W	
	Standby Power	1.35W	
Accessories	Antennas (x2), Documentation Kit		
Security	Kensington® Security Slot		
Available Color	Black		
Weight	1.9kg (4.2lbs)		
Dimensions (L x W x H)	246.2 x 265.4 x 32.2mm (9.7' x 10.4' x 1.3')		