



i3TOUCH V-Series

V1165 4K

iINTERACTIVE

- Up to 20 touch points
- V-SENSE touch technology: Finger, stylus or any other pen or finger shaped object.

iINSPIRING

- Plug & play in Windows, Macintosh and Linux
- Gestures recognition
- Extremely fast V-Sense touch technology
- LED version, 50% energy-saving

iINTEGRATED

- Built-in audio amplifier and speakers
- Professional panel for extensive daily use
- Full range of i3TOUCH displays
- Warranty: 3 years standard warranty (upgradeable)



All i3TOUCH products are compatible with Windows, MAC and Linux!

PRODUCT INFORMATION

Model name	i3TOUCH V1165 4K
Product series	i3TOUCH V-Series - Interactive Flat Panel Displays
Product order code	VSV0005803

DISPLAY SPECIFICATIONS

Panel technology	Liquid Crystal Display (LCD) with DirectLED lighting	
Panel active screen area	1429 x 804 mm	56.3" x 31.7"
Maximum display resolution	UHD – 3840 x 2160 px	
Brightness	450 cd/m ²	
Contrast ratio	1200:1	
Viewing angle	178° / 178°	
Colour depth	1.073 billion colors (10 bit)	
Response time (typ.)	6 ms	
Refresh rate	60 Hz (@ UHD)	
Pixel pitch	0.4935 x 0.372 mm	
Supported orientation	Landscape	

CONNECTIVITY

Digital AV inputs	1x HDMI 2.0 1x HDMI 1.4
Analogue AV input	1x VGA + 3.5 mm audio jack (TRS connector)
Digital audio output	1x SPDIF
Analogue audio output	1x 3.5 mm audio jack (TRS connector)
USB data ports	1x USB 3.0 2x USB 2.0
Integrated PC slot	OPS-PC bay (JAE TX24 connector)
Control input	1x COM DE-9 (RS-232)
Network	1x RJ45 LAN
Integrated loudspeakers	2x 16 Watt

OPERATIONAL FEATURES

Operating system	Android™ 5.0 Lollipop
Architecture	CPU : ARM Cortex A53 (1.4 GHz) GPU : Mali-450 RAM : 2 GB ROM : 16 GB
Interactive touch	Technology: V-Sense Infrared Touch Input Detection: 20 touch inputs Connection: USB-B Recognition: Finger or passive stylus (size ≥ 6 mm) Response time: < 15 ms Accuracy: ± 2 mm
Supported Compatibility	Windows, Android™, Macintosh OSX
Maximum operating hours	18 hours / day

ELECTRICAL PROPERTIES

Power voltage	100 ~ 240 Volt – 50/60 Hz
Power consumption	170 Watt (standby < 0.5 Watt)

ENVIRONMENTAL CONDITIONS

Operating temperature	0° C to 40° C
Operating humidity	0% to 60% RH non-condensing
Storage temperature	-10° C to 60° C
Storage humidity	0% to 80% RH non-condensing

PHYSICAL PROPERTIES

Product dimensions	1519 x 895 x 114 mm	59.8" x 35.3" x 4.5"
Net product weight	61 kg	
Packaging Size	1660 x 1045 x 245 mm	65.4" x 41.2" x 9.7"
Packaged Weight	76 kg	
VESA mounting	500 x 400 mm	
Color	Black front bezel, black back cabinet	

ACCESSORIES

INCLUDED	User Manual
	Remote Control
	Power Supply Cord
	HDMI cable
	USB cable
	2x passive stylus
	VESA-universal wall mount

OPTIONAL ACCESSORIES	i3COMPUTER OPS
-----------------------------	----------------

REGULATORY INFORMATION

PRODUCT TYPE APPROVAL	CE, FCC
------------------------------	---------

TECHNICAL DRAWINGS

AUTHORISED DISTRIBUTOR	
-------------------------------	--