

## Key Features

- Lightweight, compact, and portable design with protective sleeve for easy and safe transport
- Easily extend display to a larger screen from mobile devices
- HDMI and USB-C inputs for flexible connectivity
- Find your perfect view every time with the foldable stand
- USB-C one cable flexible display setup



\*External power adaptor required for power charging

## Product **Description**

The ViewSonic VA1650 is a lightweight, portable 16" Full HD portable monitor with USB-C connectivity for power charging. Designed to boost productivity on the go, extend your screen from a phone, tablet, or laptop to a larger display anytime, anywhere. The included protective sleeve makes it effortless to safely carry and protect your monitor, whether traveling, relaxing outdoors, or simply moving around your home.

- 1. USB Type (Power)
- 2. USB Type C
- 3. HDMI
- 4. Speaker

Visit Us www.viewsonic.com



| DISPLAY                                    |                                              | CONTROLS                      |                                                                                              |
|--------------------------------------------|----------------------------------------------|-------------------------------|----------------------------------------------------------------------------------------------|
| Display Size (in.):                        | 16                                           | Physical Controls:            | Lever push key: Up, Enter,<br>Down, Return (power)                                           |
| Viewable Area (in.):                       | 15.6                                         |                               | . ,                                                                                          |
| Panel Type:                                | IPS Technology                               | On Screen Display:            | Input Select, Audio Adjust,<br>ViewMode, Color Adjust,<br>Manual Image Adjust, Setup<br>Menu |
| Resolution:                                | 1920 x 1080                                  |                               |                                                                                              |
| Resolution Type:                           | FHD (Full HD)                                | OPERATING CONDITIONS          |                                                                                              |
| Static Contrast Ratio:                     | 1,000:1 (typ)                                | Temperature:                  | 32°F to 104°F (0°C to 40°C)                                                                  |
| Dynamic Contrast Ratio:                    | 50M:1                                        | Humidity (non-condensing):    | 20% to 90%                                                                                   |
| Light Source:                              | LED                                          | WALL MOUNT                    |                                                                                              |
| Brightness:                                | 250 cd/m² (typ)                              | VESA Compatible:              | Customized, 75 mm                                                                            |
| Colors:                                    | 16.7M                                        | INPUT SIGNAL                  |                                                                                              |
| Color Space Support:                       | 8 bit (6 bit + FRC)                          | Frequency Horizontal:         | HDMI (v1.4): 15 ~ 82KHz,<br>Type C: 24 ~ 82KHz                                               |
| Aspect Ratio:                              | 16:9                                         |                               | HDMI (v1.4): 50 ~ 75Hz, Type                                                                 |
| Response Time (Typical GTG):               | 7ms                                          | Frequency Vertical:           | C: 50 ~ 75Hz                                                                                 |
| Viewing Angles:                            | 178º horizontal, 178º vertical               | VIDEO INPUT                   |                                                                                              |
| Backlight Life (Hours):                    | 30000 Hrs (Min)                              | Digital Sync:                 | TMDS - HDMI (v1.4), Micro-<br>Packet - Type C                                                |
| Curvature:                                 | Flat                                         | ERGONOMICS                    | 71                                                                                           |
| Refresh Rate (Hz):                         | 60                                           | Tilt (Forward/Back):          | 20° / 45°                                                                                    |
| Low Blue Light:                            | Software solution                            | WEIGHT (IMPERIAL)             |                                                                                              |
| Flicker-Free:                              | Yes                                          | Net (lbs):                    | 1.5                                                                                          |
| Color Gamut:                               | NTSC: 45% size (Typ)<br>sRGB: 64% size (Typ) | Net Without Stand (lbs):      | 1.5                                                                                          |
| Pixel Size:                                | 0.179 mm (H) x 0.179 mm (V)                  | Gross (lbs):                  | 3.3                                                                                          |
| Surface Treatment:                         | Anti-Glare, Hard Coating (3H)                | WEIGHT (METRIC)               |                                                                                              |
| COMPATIBILITY                              | , , ,                                        | Net (kg):                     | 0.7                                                                                          |
| PC Resolution (max):                       | 1920x1080                                    | Net Without Stand (kg):       | 0.7                                                                                          |
| Mac® Resolution (max):                     | 1920x1080                                    | Gross (kg):                   | 1.5                                                                                          |
| DO On another a Oceatame                   | Windows 10/11 certified; macOS tested        | DIMENSIONS (IMPERIAL) (WX     | (HXD)                                                                                        |
| PC Operating System:                       |                                              | Packaging (in.):              | 16.4 x 11.4 x 2.1                                                                            |
| Mac® Resolution (min):                     | 1920x1080                                    | Physical (in.):               | 14.09 x 8.29 x 0.55                                                                          |
| CONNECTOR                                  |                                              | Physical Without Stand (in.): | 14.09 x 8.29 x 0.55                                                                          |
| USB 3.2 Type C DisplayPort Alt mode only : | 1 (65W power charger)                        | DIMENSIONS (METRIC) (WXH      | XD)                                                                                          |
| 3.5mm Audio Out:                           | 1                                            | Packaging (mm):               | 416 x 290 x 54                                                                               |
| HDMI 1.4:                                  | 1                                            | Physical (mm):                | 357.8 x 210.5 x 13.9                                                                         |
| Power in:                                  | USB Type C (power only)                      | Physical Without Stand (mm):  | 357.8 x 210.5 x 13.9                                                                         |
| AUDIO                                      | CCD Type C (perior omy)                      | GENERAL                       |                                                                                              |
| Internal Speakers:                         | 1Watts x2                                    | Regulations:                  | CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC,                                                 |
| POWER                                      |                                              |                               | UkrSEPRO                                                                                     |
| Eco Mode (Conserve):                       | 6W                                           | PACKAGE CONTENTS:             | VA1650 x1, USB Type-C<br>Cable (Male-Male) x1, Quick<br>Start Guide x1, Sleeve case<br>x1    |
| Eco Mode (optimized):                      | 6.5W                                         |                               |                                                                                              |
| Consumption (typical):                     | 7W                                           |                               | Please dispose of in                                                                         |
| Consumption (max):                         | 8.5W                                         | Recycle/Disposal:             | accordance with local, state or federal laws.                                                |
| Voltage:                                   | DC 5V/9V/12V/15V/20V                         |                               | *Warranty offered may differ                                                                 |
| Stand-by:                                  | 0.5W                                         | Warranty:                     | from market to market                                                                        |
|                                            | 0.0                                          |                               |                                                                                              |
| Power Supply:                              | External (Optional)                          |                               |                                                                                              |

