



## 10G PoE++ Injector

One 95 W Port, IEEE 802.3bt (4PPoE) Compliant, Plastic Housing, Wall-mount Option

SKU: 561945 | EAN-13: 0766623561945 | UPC: 766623561945

### Next-gen 10 Gbps 95 W 4PPoE Injector - Supports 10/100/1000/2500/5000/10,000 Mbps and Power over Ethernet 802.3bt

The Intellinet Network Solutions 10G PoE++ Injector lets you connect your IEEE 802.3bt/af/at-compliant wireless access point, IP phone, network camera and more to a non-PoE LAN switch port while providing the necessary PoE power up to 100 meters (328 ft.). This 10-Gigabit 4PPoE Injector has an output power rating up to 95 watts, which is enough for even very power-hungry PoE++ devices like motorized PTZ cameras, thin clients, point-of-sale systems, lighting controllers and digital signage applications.

### Full backward-compatibility with existing IEEE 802.3af/at Power over Ethernet devices

The Intellinet Network Solutions 10G PoE++ Injector helps you connect your IEEE 802.3bt/af/at-compliant products to a non-PoE LAN switch port. The Injector features auto-sensing technology, so it always delivers the correct wattage the device needs, whether it's PoE (up to 15.4 W), PoE+ (up to 30 W) or PoE++ (up to 95 W).

### Reduced wiring costs

It's no longer necessary to run AC power lines for your wireless access point, network camera or IP phone. Simply connect this PoE++ Injector to a LAN switch port, and use the existing network cabling to deliver DC power as well as transfer data.

### Safe protection for your expensive network equipment

The auto-sensing technology of this high-power PoE Injector ensures that your products are protected from power problems like short circuits (short GND), current overloads and high voltages. Port surge protection up to 6 kV and ESD protection up to 8 kV make its safety complete.

### Wall-mount option

For full installation flexibility, you can mount the injector on the wall through four built-in fixing points on the back panel.

### Features:

- Power over Ethernet with output up to 95 watts
- Ultra-fast 10GBASE-T RJ45 Ethernet port, IEEE 802.3bz compliant
- Compatible with IEEE 802.3bt/at/af-compliant powered devices (PD) such as network cameras, wireless access points, VoIP phones and more
- Distance support up to 100 m (328 ft.)

For more information on Intellinet products, consult your local dealer or visit [www.intellinet-network.com](http://www.intellinet-network.com).

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- Internal power supply
- Auto-sensing PoE awareness to ensure that power is only sent to IEEE 802.3bt/at/af-compliant devices; non-PoE devices only receive data
- Short-circuit, overload and high-voltage protection
- Grounding point to protect equipment from external electrical surges
- Port surge protection up to 4 kV
- ESD protection up to 8 kV (air) and 6 kV (contact)
- Built-in wall-mounting holes and four rubber feet for desktop use
- Earthing kit included
- Ideal for power-hungry IoT devices like motorized IP cameras, thin clients, PoE lighting and more
- Saves time and money by delivering data and power via existing network cables
- Plug-and-play installation; no configuration required
- Fully NDAA-compliant
- Three-year warranty

## Specifications:

### Standards

- IEEE 802.3af (Power over Ethernet)
- IEEE 802.3at (High-Power PoE+ Power over Ethernet)
- IEEE 802.3bt (PoE++/4PPoE/Ultra Power over Ethernet)
- IEEE 802.3 (10Base-T Ethernet)
- IEEE 802.3u (100Base-TX Fast Ethernet)
- IEEE 802.3ab (1000BASE-T Gigabit Ethernet)
- IEEE 802.3bz (2.5G/5G/10GBASE-T Ethernet)

### General

- Media support:
  - 10Base-T Cat3/4/5/5e/6/6a UTP/STP RJ45
  - 100Base-TX Cat5/5e/6/6a UTP/STP RJ45
  - 1000Base-T Cat5e/6/6a UTP/STP RJ45
  - 2.5G/5GBase-T Cat5e/Cat6/6a UTP/STP RJ45
  - 10GBase-T Cat6/6a or higher UTP/STP RJ45
- Ports:
  - One RJ45 10G data input port
  - One RJ45 PoE power + 10G data output port
- Certifications: CE, RoHS, FCC Class A, UKCA, NDAA
- PoE Pinout
  - Pin 1: DC (-)
  - Pin 2: DC (-)
  - Pin 3: DC (+)
  - Pin 4: DC (+)
  - Pin 5: DC (+)
  - Pin 6: DC (+)
  - Pin 7: DC (-)
  - Pin 8: DC (-)

### LEDs

- Power
- PoE
- PoE max

DIP switch functions to select the PoE standard of the connected PD:

- 802.3bt (for fully compliant 802.3bt/at/af PDs)
- UPoE (for PDs that support the maximum power from PSE over four pairs, regardless of the PD class, including Cisco Universal Power over Ethernet)
- Legacy 802.3bt (for PDs not in full compliance with 802.3bt/at/af)

### Power

- Internal power supply:
  - Input: 100.0 - 240.0 VAC, 50 - 60 Hz
  - Output: DC, 54.0 V, 1.76 A
  - PoE budget: 95.0 watts (maximum)
  - Power consumption: 100.0 watts (maximum)

### Physical

- Plastic housing
- Dimensions (L x W x H): 172 x 100 x 40 mm (6.77 x 3.94 x 1.57 in.)
- Net weight: 500 g (1.1 lbs.)
- Gross weight: 877 g (1.93 lbs.)

For more information on Intellinet products, consult your local dealer or visit [www.intellinet-network.com](http://www.intellinet-network.com).

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- Operating temperature: 0 - 40°C (32 - 104°F)
- Storage temperature: -40 - 70°C (-4 - 194°F)
- Operating humidity: 10 - 90% RH, non-condensing
- Storage humidity: 5 - 90% RH, non-condensing

## Package Contents

- 10G PoE++ Injector
- Power cable
- Earthing kit
- Instructions



For more information on Intellinet products, consult your local dealer or visit [www.intellinet-network.com](http://www.intellinet-network.com).

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.