Muliple Screen Split-Ultra HD Signage Ultra HD UH5C Series



you to create various formats of content to deliver commercial message effectively. Also, it is enhanced in content management. With LG SuperSign EZ providing basic content templates, you can create and edit content simply and quickly on your mobile device or signage display.

Key Features



Ultra HD Resolution (3840x2160)

Ultra HD Large screen delivers immersive viewing experience by 4 times higher definition picture guality than FHD.



High Efficiency Video Coding

Supports HEVC-based content which has the double data compression ratio than the H.264, so network traffic can be reduced by half.



Conventional H.264



UH5C

Multiple Screen

Multiple Screen with PBP or PIP



PBP (Picture-By-Picture) and PIP (Picture-In-Picture) feature gives a chance to compose up to 4 divided split screen on landscape or portrait display format.







PBP - Landscape

PBP - Portrait



Business

Solutions

Muliple Screen Split-Ultra HD Signage Ultra HD UH5C



Other Features

Smart Platform

Quad Core SoC*

The High Performance SoC can execute several tasks at the same time and provides smooth content playback.



*SoC : System-on-Chip

webOS 2.0

The webOS 2.0 platform provides powerful and convenient tools to create, including app development materials.



Space Management Efficiency

Slim

Slimmer Depth

With its slim depth and built-in speaker, which increases space efficiency, you don't need to install an extra media player. Also, you can move it conveniently with its handle on the back side.



Easy Maintenance

Real-Time Remote Monitoring

When an alarm occurs, an e-mail notification is sent using SuperSign C or SI SW through the SNMP Protocol. In case of malfunctions or errors, real-time remote care is available.



Embedded Template by SuperSign EZ

You can edit contents not only on your smart phone but also on your PC very easily and conveniently at any time.



Supportive Convenience

BEACON

With BEACON and Bluetooth Low Energy (BLE) supported by UH5C, retail stores can provide coupons and information in real-time.



OPS* Kit / HDBaseT Box

The UH5C provides an OPS Kit to connect a third-party OPS player or HDBaseT box. Users have the flexibility to choose any media player as long as it complies with the OPS.




*OPS : Open Pluggable Specification

Dimension

86"


75.8" x 43.4" x 2.5" / 108lbs (Without handle) 75.8" x 43.4" x 3.1" (With handle) *Without logo






75"

66.2" x 37.8" x 2.3" / 91.5lbs (Without Handle) 66.2" x 37.8" x 2.9"(With Handle) *Without logo







Specifications

UH5C		86UH5C-B	75UH5C- B	
PANEL	Screen Size	86"	75"	
	Panel Technology	IPS	IPS	
	Aspect Ratio	16:9	16:9	
	Native Resolution	3,840 × 2,160 (UHD)	3,840 x 2,160 (UHD)	
	Brightness	500cd/m ²	500cd/m ²	
	Contrast Ratio	1,200:1	1,200:1	
	Dynamic CR	4,000,000:1	4,000,000:1 (DTV Label only)	
	Viewing Angle (H x V)	178 x 178	178 x 178	
	Response Time	8ms (G to G)	6ms (G to G)	
	Surface Treatment	Low Haze 3%	Low Haze 3%	
	Life time (Min.)	50,000 Hours	50,000 Hours	
	Guaranteed Operation Hours	24 Hours	24 Hours	
	Orientation	Portrait & Landscape	Portrait & Landscape	
CONNECTIVITY	Input	HDMI, DP, DVI-D, Audio, USB 3.0, SD Card	HDMI, DP, DVI-D, Audio, USB 3.0, SD Card	
	Output	DP, Audio	DP, Audio	
	External Control	RS232C, RJ45, IR Receiver, Pixel Sensor	RS232C, RJ45, IR Receiver, Pixel Sensor	
PHYSICAL SPECIFICATION	Bezel Color	Black	Black	
	Bezel Width	14.7mm	14.9mm	
	Monitor Dimension (W x H x D)	75.8" x 43.2" x 2.4" (without Logo/Handle)	66.2" x 37.8" x 2.3" (without Logo/Handle)	
	Weight (Head)	108lbs	91.5lbs	
	Carton Dimensions (W x H x D)	81.6" x 49.6" x 11.5"	71.5" x 44.2" x 9"	
	Packed Weight	134.7lbs	109.1lbs	
	VESA [™] Standard Mount Interface	600 x 400mm	600 x 400mm	
SPECIAL FEATURES		Temperature Sensor, Auto Brightness Sensor, Tile Mode (up to 15x15), Natural Mode@Tile Mode, ISM Method, Internal Memory, Wi-Fi built-in, USB Cloning, Contents Scheduling, Sync mode, PM mode, Fail Over, Wake on LAN, BEACON (On/Off), Embedded Template		
ENVIRONMENT	Operation Temperature Range	32°F to 104 °F	32°F to 104 °F	
CONDITIONS	Operation Humidity Range	10 % to 80 %	10 % to 80 %	
POWER	Power Supply	100-240V~, 50/60Hz	100-240V~, 50/60Hz	
	Power Type	Built-In Power	Built-In Power	
	Тур.	275W	240W	
	Power Smart Energy Consumption Saving	193W	170W	
STANDARD (CERTIFICATION)	Safety	UL / cUL / CB / TUV / KC	UL / cUL / CB / TUV / KC	
	EMC	FCC Class "A" / CE / KCC	FCC Class "A" / CE / KCC	
	ErP / Energy Star	No / No	No / No	
MEDIA PLAYER	OPS type compatible	Yes	Yes	
COMPATIBILITY	External Media player Attachable	Yes (MP500/MP700)	Yes (MP500/MP700)	
SOFTWARE COMPATIBILITY	SuperSign W-Lite	Yes	Yes	
	SuperSign C	Yes	Yes	
ACCESSORY	Basic	Remote Controller (include 2ea batteries), Power Cord, QSG, DP 1.8M, Regulation Book, Phone to RS232C Gender, Memory Cover	Remote Controller (include 2ea batteries), Power Cord, QSG, DP 1.8M, Regulation Book, Phone to RS232C Gender, Memory Cover	
	Optional	Pixel sensor(KT-SP0), Media player, OPS Kit(KT-OPSA)	Pixel sensor(KT-SPO), Media player, OPS Kit(KT-OPSA	
		Built-In (20W (10W x 2))		
PEAKERS		Built-In (2000	(10W x 2))	
PEAKERS	UPC	7 19192 19990 3	(10W × 2)) 7 19192 19924 8	

Connectivity



Download LG Commercial Display Mobile App



More info Lg.com/us/commercial You Tube youtube.com/LGCommercialDisplayUSA

LG may make changes to specifications and product descriptions without notice. Copyright © 2016 LG Electronics Inc. All rights reserved. "LG Life's Good" is a registered of LG Corp. The names of products and brands mentioned here may be the trademarks of their respective owners. LG_SPEC_UH5C_061616_a



