wePresent WiPG
Wireless interactive Presentation Gateway

WiPG - 1000

Wireless interactive Presentation Gateway

Link PC, Mac, Pad, Mobile, Projector or Display all together to make professional and interactive presentation.
(Full HD Support)

Revolutionary "interactive" features and "Mobile" application

■ **Remote Desktop Support**
Use a set of mouse and keyboard connected to WiPG-1000 to control the projecting PC/Mac.

■ **SidePad**
Use iPad/iPhone or Android Pad/Phone to control the projecting PC/Mac.

■ **BrowserSlides**
Allow audience to use web browser to view the speaker's slides and save them for taking notes.

■ **Two-way Wireless Projection Control**
Select a PC/Mac from WiPG starting screen or its web page to make projection

■ **WiFi-Doc**
Project MS-office file (doc, xls, ppt) & PDF document from iPad/iPhone or Android Pad/Phone

■ **IWB-Intelligent White Board Support (selected model)**
Speaker and audience interact on IWB wirelessly

Enhanced features

■ **Full HD Support**
Support video output up to 1920x1080 through HDMI, 1600x1200 through VGA interfaces

■ **FPnS Plus**
Fast Plug&Show+ with 30 FPS & audio projection for Win XP/Vista/7 & Mac

■ **4-to-1 Plus**
30 FPS quadrant screen projection for Win XP/Vista/7 & Mac

■ **Conference control Plus**
Web-based mediator function and new standby screen PC-list design

| Support OS | Windows 7 | Windows Vista | Windows XP | Windows Mobile 6.5 | MAC OS |

wePresent WiPG
Wireless interactive Presentation Gateway

Basic features

Windows/Mac support
MobiShow for iOS/Android/Blackberry
Plug&Show: launching the projection application from a USB thumb drive
4-to-1 Quadrant Screen Projection
SNMP Manager: manage/configure multiple WiPGs thru SNMP consoles
Conference Control: Mediator control function thru the device web page
Support up to 64 logged users
Security design: Session Login Code, WEP/WPA key, and GateKeeper
HDMI and VGA dual video interfaces
WiFi AP-Client mode support
WiFi 802.1b/g/n

Specification

Standards	IEEE 802.11b/g/n 2.4GHz
	IEEE 802.3 (10BASE-T) / IEEE 802.3u (100BASE-TX)
Security	IEEE Standard 64/128 bit WEP / WPA / WPA2-PSK
Management	Web-based configuration
Supported Output Resolution	VGA:SVGA(800x600)/XGA(1024x768)
	/WXGA(1280x768)/WXGA(1280x800)/WXGA(1360x768)
	/ WXGA+(1440x900)/UXGA(1600x1200)
	HDMI:720p(1280x720)/1080p(1920x1080)
Supported Operation System	Windows XP / Vista / 7, Mac OS X 10.5 and above,
	Android 2.2 and above, iOS 3.2 and above.
Power	External power adaptor DC 5V 2.6A
Interfaces	15Pin VGA
	HDMI
	RJ-45
	USB 2.0 x 3
	Power Button
	Reset Button
	Stereo Phone Jack
Certificate	FCC/CE