



**High Performance, High resolution Widescreen Installation WUXGA (1920 x 1200) Projector with HDBaseT™, 3D Surround Sound Audio and 3D Video Ready**

**Features**

- High 5500 lumens of brightness with a 10,000:1 contrast ratio
- Native WUXGA (1920 x 1200) DLP® dark chip 3 and BrilliantColor™ technologies for sharp and detailed image quality
- Centered lens for easy installation
- Horizontal and Vertical lens shift
- Horizontal and Vertical Keystone correction
- HDBaseT™ interface with support for distribution of HD video and digital audio content over CAT5e/6LAN cable
- MHL device compatibility for streaming of video and audio content from a compatible mobile device
- Full 3D capability for Blu-Ray and Broadcast
- 3D sync port for compatibility with IR (infrared) 3D passive
- 14W of total 3D audio surround sound power (7W x 2) with multiple audio-in and audio-out ports
- 12V trigger for simple screen/projector automation port for direct communications and automated control of such devices as screens and curtains
- RJ45/RS-232c for integration and system automation compatible with Crestron, AMX, Extron, and Telnet
- Top-loading, sliding cover for quick and easy lamp replacement
- Keypad lock prevents accidental system adjustments
- Dual remote infrared sensors (Front and Rear)
- Anti-theft security features: Kensington® security slot, and security bar



Specifications				
<b>Brightness (Typical)</b>	5500 ANSI Lumens			
<b>Native Resolution</b>	WUXGA (1920 x 1200)			
<b>Max. Resolution</b>	WUXGA (1920 x 1200) @60Hz			
<b>Contrast Ratio</b>	10,000:1 (Full On/Off)			
<b>Lamp Life and Type</b>	1,500/3,500 Hours (Normal/Eco), 370W/280W			
<b>Lamp Part #</b>	5811119760-SVV			
<b>Display Type</b>	Single 0.67" DLP® Technology by Texas Instruments			
<b>Throw Ratio (±3%)</b>	1.25 to 2.13:1 (Distance/Width)			
<b>Image Size (Diagonal)</b>	21.8" to 371.4"			
<b>Projection Distance</b>	3.28' to 32.8' (1.0 to 10 m)			
<b>Projection Lens</b>	F=2.45 – 3.22, f=18.8 – 32mm			
<b>Zoom Ratio</b>	1.7:1 Manual Zoom/Focus			
<b>Aspect Ratio</b>	16:9 Native, 4:3 Compatible			
<b>Offset</b>	122.4% / 111.2%			
<b>Keystone Correction</b>	± 30° Vertical, Horizontal ± 25°			
<b>Color Spectrum</b>	1.07 Billion			
<b>Horizontal Scan Rate</b>	15, 31 ~ 91.4KHz			
<b>Vertical Scan Rate</b>	24 ~ 30Hz, 47 ~ 120Hz			
<b>3D Functionality</b>	Full 3D (Via DLP® Link™, Blu-ray and Broadcast 3D)			
<b>Speaker</b>	3D Audio Surround Sound (7Wx2)			
<b>Lens Shift Range</b>	Vertical: +29%, -13% Horizontal: +/-10%			
<b>Remote Control</b>	Fully Featured IR Remote			
<b>Projection Method</b>	Table Top or Ceiling Mount (Front or Rear)			
<b>Uniformity</b>	85%			
<b>Computer Compatibility</b>	WUXGA, UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized; VESA Standards; PC and Macintosh Compatible			
<b>Video Compatibility</b>	HDTV (1080i/p, 720p), SDTV(480i, 576i), EDTV (480p, 576p), SDTV(480i, 576i), NTSC 4.43, PAL B/G/H/I/M/N 60, SECAM			
<b>I/O Connection Ports</b>	HDMI v1.4 (x2)	HDMI 1/MHL	Microphone-In (Mini-Jack)	
		HDMI 2	12-Volt Trigger (Mini-Jack)	
	VGA-In (x2)	3D Sync		
	VGA-Out	RJ45		
	DVI-D	RS-232		
	Component/RGBHV (5 BNC)	Power-Out (5V/2.0A) USB Type A		
	S-Video	Wire Remote In/Out (Mini-Jack)		
	Composite	Service Only (USB Type B)		
	Audio-In	RCA L/R	Audio-Out	RCA L/R
		Mini-Jack (X3)		Mini-Jack
<b>HDBaseT™</b>				
<b>Security</b>	Kensington® Lock Port, Security Bar			
<b>Weight</b>	18.5lbs (8.4kg)			
<b>Dimensions (W x D x H)</b>	17.5" x 12.9" x 6.3" (445 x 330.2 x 162mm)			
<b>Noise Level</b>	30dB/36dB (Eco/Normal)			
<b>Power</b>	Supply: AC 100-240V, 50/60Hz Consumption: 380W/480W (Eco/Normal) <0.5W (Standby Mode), <6W (LAN Standby)			
<b>Operating Temperature</b>	41 to 104°F (5 to 40°C)			
<b>Warranty</b>	3-Year Limited Parts/Labor, 1-Year Lamp			
<b>Standard Accessories</b>	AC Power Cord, VGA Cable, Remote Control, Batteries for Remote, User Manual (CD), Warranty Card			
<b>Optional Accessories</b>	Wireless Collaboration System NovoConnect B360			
	Wireless Collaboration System NovoPro			
	Replacement Lamp			
<b>UPC</b>	813097020369			

